

ezEX® 38 Connectors



EXO Crimp Frame +
EXO-EX Die crimps
ALL ezEX-RJ45
Connectors

The **ezEX-RJ45 Connector Series** has expanded. The new ezEX38 joins forces with the ezEX®44 and ezEX®48. They now cover an insulation diameter range of 0.033 through 0.048 inches. The ezEX38 will typically be used on Cat5e and smaller Cat6 cabling. The ezEX38 features the same unique integrated patented Hi-Lo stagger load bar, allowing the conductors to pass through the front end of the connector making it easy to verify the wiring sequence before terminating. The termination tool for these connectors is the EXO Crimp Frame® and EXO-EX Die™ (100061C).

- Hi-Lo stagger to isolate each conductor
- Simple one piece/pass through design, no bars or liners
- 50 micron gold plated contacts
- Insulation Diameter (Conductor)
 - Size range ezEX38: 0.033" – 0.038" (0.84 – 0.97mm)
- Max Outer Diameter:
 - Shielded: 0.290" (7.36mm)
- Solid or Stranded 24-22 AWG
- RoHS, UL, TIA, TAA, & FCC compliant
- Made in the USA



Ordering Information

ezEX38 - ezEX-RJ45 Unshielded

P/N	Description	UPC Codes
100046C	ezEX38 Connectors, 10/Clamshell.	849160011217
100047C	ezEX38 Connectors, 50/Clamshell.	849160011026
202038J	ezEX38 Connectors, 100/Jar.	849160011019
105023	ezEX38 Connectors, Bulk. 500/Bag.	849160011200



California, USA

Phone: 805.384.2777 / 800.749.5783 • Fax: 800.749.5784

www.platinumtools.com