

**Description:** 16AWG Multicore LSHF speaker cables. Oxygen free copper conductors, features a quick strip jacket for easy installation




### Construction

Conductor Material : 99.999% Oxygen Free Bare Copper  
 Number of Strands : 41/0.2mm  
 Insulation Material : Low Smoke Halogen Free (LSHF)  
 Sheath Material : Low Smoke Halogen Free (LSHF)  
 Sheath Colour : See Table  
 Core Identification : 2 Core – Red & Black  
 : 4 Core – Red, Black, Green & White

### Electrical Characteristics

Nominal Conductor Resistance : < 13.7  $\Omega$ /km  
 Insulation Resistance : > 200 M $\Omega$ .M  
 Voltage Rating : 450/750V  
 Test Voltage : 2.5kV for 5 Minutes

### Physical Characteristics

Overall Diameter : See table  
 Min. Bend Radius : 10 x OD  
 Temperature Rating : 0°C to +70°C  
 Weight : See table

### Standards

CE Complaint : LVD (2006/95/EC)  
 RoHS Complaint : Yes

Part No.	No. Cores	Outer Sheath Colour	Weight (kg/km)	OD (mm)
TSS16/2H	2	Violet	35	6.1
TSS16/2HW	2	White	35	6.1
TSS16/2H08	2	Orange	35	6.1
TSS16/4H	4	Violet	54	7.1
TSS16/4HW	4	White	54	7.1
TSS16/4h08	4	Orange	54	7.1